24" (23.6" viewable) Ultra HD Multimedia LED Monitor



3840x2160 Resolution for a Stunning Entertainment Experience

VX2475Smhl-4K





Whether you're playing graphic-intense video games, watching action-packed movies, or editing detail-rich photos, the ViewSonic® VX2475Smhl-4K is the monitor you need to bring your multimedia to life. With stunning 3840x2160 resolution and SuperClear® PLS panel technology, this monitor is engineered to deliver the ultimate in detail and clarity to provide an incredible entertainment experience. What's more, with true Ultra HD resolution at 60Hz, this monitor delivers smooth, crisp images without any streaking, blurring, or ghosting—perfect for fast-paced gaming, as well as for watching sports and movies. When smooth screen performance and clarity of detail is critical to your entertainment needs, the ViewSonic VX2475Smhl-4K Ultra HD monitor delivers.

Key Features:

Ultra HD 3840x2160 @ 60Hz* native resolution for ultra-high definition multimedia applications

SuperClear® PLS panel technology for stunning color performance and wide-angle viewing

Future-proof DisplayPort, HDMI, and MHL inputs

Exclusive ViewMode[™] technology delivers superior color rendering and intuitive settings

Flicker-Free and Blue Light Filter technology provide more comfortable viewing

Designed for:

Gaming

Entertainment

Photography/Graphics applications

24" (23.6" viewable) Ultra HD Multimedia LED Monitor



VX2475Smhl-4K



Specifications

LCD PANEL	Type Display Area Optimum Resolution Brightness Contrast Ratio Viewing Angles Colors Response Time Backlight Life Panel Surface	Color a-Si Active Matrix TFT LCD 20.5" horizontal x 11.5" vertical; 23.6" diagonal 3840x2160 300 cd/m² (typ.) 1,000:1 (typ.) 120,000,000:1 178° horizontal, 178° vertical 16.7M (true 8-bit) 4ms (GTG) White-light LED 30,000 hours (min.) Anti-glare, hard-coating (3H)	ERGONOMICS
			POWER
			OPERATING CONDITIONS
			DIMENSIONS (W x H x D) Phy
VIDEO INPUT	Digital Frequency Sync	HDMI/MHL, HDMI, DisplayPort Fh: 24~160kHz, Fv: 50~75Hz Separate Sync, Composite Sync, Sync on Green	WEIGHT
AUDIO OUTPUT	Speakers	3-watt (x2)	WALL MOUNT
COMPATIBILITY	PC Mac®	Up to 4096x2160 non-interlaced Up to 4096x2160	REGULATIONS
CONNECTOR	Video In Audio Out Power	HDMI/MHL 2.0, HDMI 2.0, DisplayPort 1.2a 3.5mm mini jack External power adapter	RECYCLE/DISPOSAL
CONTROLS	Front Panel Buttons OSD	Power, 1, Up, Down, 2 Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)	WARRANTY

ERGONOMICS	Tilt	Forward 5° / Back 22°
POWER	Voltage Consumption Optimize Conserve	AC 100–240V (universal), 50 / 60Hz 35W (typ.) / 50W (max.) 26W (typ.) 20W (typ.)
OPERATING CONDITIONS	Temperature Humidity	32–104° F (0–40° C) 10–90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with Stand Physical without Stand Packaging	22.3 x 17.15 x 9.1 in. / 566.4 x 435.5 x 231.5mm 22.3 x 14.0 x 1.9 in. / 566.4 x 356.6 x 48.0 mm 24.7 x 17.7 x 4.9 in. / 626 x 449 x 124 mm
WEIGHT	Net with Stand Net without Stand Gross	10.1 lb. / 4.6 kg 8.1 lb. / 3.7 kg 14.3 lb. / 6.5 kg
WALL MOUNT	VESA	100 x 100 mm
REGULATIONS		CE, CB, RoHS, ErP, REACH, WEEE, TCO, WHQL, UL, FCC-B, ENERGY STAR 6.0, EPEAT gold, Mexico, Mexico energy, Windows 8
RECYCLE/DISPOSAL		Please dispose of in accordance with local, state, or federal laws
WARRANTY		Three-year limited warranty on parts, labor and backligh

Optional Accessories

ViewSonic HDMI male to DVI male cable 1.8 meter	CB-00008948
Mini DisplayPort cable, 1.8m	CB-00010958
DisplayPort cable Male to Male 9.2m 28AWG	CB-00010684
DisplayPort cable	CB-00010555
DisplayPort to DVI Adapter	LCD-CABLE-001

What's in the box?

VX2475Smhl-4K monitor, Power adapter, Power cable, HDMI cable, Quick Start Guide, ViewSonic Wizard CD (User Guide)













