

(VXL)

High Performance Desktop Thin Client



Itona F24 Series

Key Features

- Windows Embedded Standard 7 operating system
- VIA Nano U3300 1.2 GHz processor
- North Bridge: VIA VX900
- Graphic Processor: Integrated Chrome9 HD DX 3D/2D
- Highly reliable fan-less design
- Low power consumption -Energy Star certified
- RAM: DDR3 SO DIMM
- Built-in speaker
- 8 USB Ports
- Optional Serial Port
- Built-in Gigabit LAN
- Ericom PowerTerm Terminal Emulation

The Ideal Desktop Client

Seen and not heard – that's Itona. That's because its fan-less design ensures virtually silent operation. And, its compact design and footprint makes it the ideal desktop solution.

Green Credentials

F24 series is extremely energy efficient. It is Energy Star certified with an average power consumption of 10 Watts. A flexible, expandable, 1.2 GHz high performance desktop thin client designed to deliver excellent multimedia capabilities. The new Itona F24 series represents a significant advance in the provision of low cost server based computing. The Itona F24 series has superior build quality and advanced features including 8 USB ports, powerful VIA Nano processor and supports dual display facility in extended and mirror mode.

The thin client is not only powerful and innovative, but also environment friendly and durable. The efficient external power supply combined with fan-less design ensures extremely low and reliable power consumption.

This product includes an impressive three year warranty backed by a worldwide support network. The Itona F24 Series represents an unbeatable combination of affordability, quality, performance and service.



About VXL

VXL is one of the world's largest suppliers of thin clients. Established in 1976, VXL has grown steadily and now has over two hundred employees worldwide-with offices in Germany, France, Singapore, India, the United States of America and the United Kingdom. The company's headquarters is in Bangalore, India.







Ordering Codes

F24 - F9R7 8 GB Flash/2 GB RAM F24 - F9R7W3 8 GB Flash/2 GB RAM/Wireless LAN

Model

F24 Windows Embedded Standard 7 (WES7-E)

VXL

Processor

- VIA Nano U3300 1.2 GHz processor
- North Bridge: VIA VX900
- Graphic Processor: Integrated Chrome9 HD DX9 3D/2D

Display Support

- Automatic DDC for setting resolution and refresh rate
- Display Resolution: VGA: 2048 x 1536 , 75Hz 16/32 bit colour DVI-I: 1920 x 1200 , 60Hz 16/32 bit colour.

Front Panel

- Power Button
- 2 x USB
- Mic
- Headphone

Rear Panel

- . 2 x Serial Ports
- 6 x USB 2.0
- PS/2 Keyboard
- PS/2 Mouse 1 x DVI-I Port
- 1 x VGA Port

Networking

- Gigabit LAN
- Wake on LAN

Optional

- Serial Port
- Smart card reader
- Wireless LAN donale* *Ordering Code F9R7W3

Power Consumption

- Idle state: 10.3 W
- Off state: 1.82 W

External Power Adapter

- Worldwide auto-sensing 100-240 V AC
- DC output 12V 5A

Operating Environment

- Operating Temperature: 0 to 40 °C
- Storage Temperature: -20 to 60 °C

France

Humidity: 20% to 80% RH non-condensing

Physical Characteristics

- Dimensions: 229 mm (H), 226 mm (D) 50 mm (W)
 - Weight: 2.6 Kg Approx

Software

Ericom PowerTerm Terminal Emulation

RDP Client 8

- Citrix ICA Client 14.0
- Internet Explorer 8: HTML, MHTML, XML, Active X, Media Player 12.0, Citrix Web Client
- VMware View Client 5.3
- **VPN** Support
- VNC Server/Viewer
- Microsoft Silverlight 5.1
- .Net Framework 3.5
- Dial-up support
- Local printing support
- Network printing support
- ThinPrint support 8.6
- WMI support
- Device Update Agent
- Bluetooth Support
- Plug-ins: Adobe Acrobat Reader 11.0.3, Adobe Flash 10.0

Server OS Compatibility/Support

- Microsoft Windows Terminal Server Edition, Windows server 2003/2008
- Citrix XenApp / Citrix Presentation Server/ Citrix XenDesktop
- Protocol Support :TCP/IP, NTP, DHCP, FTP, HTTP

Setup and Configuration

Boot from local flash WES7-E user interface language: US English (Default)

Optional add-ons: French, German, Spanish, Italian, Dutch, Turkish, Japanese

- Keyboard Language support: US English
- standard 36 other languages supported. Scanners & Camera Support
- VPN
- Customizable ThinPrint
- PPP/Dial-up-Networking
- USB input devices support
- My ODBC Client support











Head Office: 'House of Excellence', No 17 Electronics City, Hosur Road, Bangalore 560 100, India. Tel: +91 80 28523252/3 Fax: +91 80 28520095 E-mail: sales@vxl.net Web: www.vxl.net European Headquarters: Carrington Business Park, Carrington, Manchester, UK M31 4DD. VXL Instruments Limited Tel: +44 (0) 16 17 75 47 55 Fax: +44 (0) 16 17 75 48 66 E-mail: sales@vxl.net



Tel: +33 (0) 1 42 17 00 03 E-mail: sales@vxl.net

Tel: +49 (0) 8761 1093 E-mail: sales@vxl.net

Tel: +1 281 305 1800 E-mail: sales@vxl.net

Singapore

Tel: +65 6278 8180 E-mail: sales@vxl.net

Management

- Remote management, configuration and upgrades through XLmanage client management software
- Wake terminal remotely (Wake-on-LAN)
- Terminal configuration (IP information, name, etc)

CE, FCC, TUV-GS, cTUVus, CCC, C-Tick,

R-Gost, VCCI, BIS Certified

Energy and Environment:

RoHS, WEEE, Energy Star 5.2

Three years limited warranty

- Remote shadowing
- Reporting

Warranty

Regulatory Compliance

Safety and EMC: