

1 Port PCI Express Low Profile Parallel Adapter Card - SPP/EPP/ECP

StarTech ID: PEX1PLP



The PEX1PLP PCIe Parallel Adapter card can be installed in a PCI Express (PCIe) x1 slot, allowing you to connect EPP/ECP parallel peripherals to any computer, while relying on a native, single-chip design (Oxford OXPCle952) that harnesses the capability of true PCI Express - ensuring maximum performance and reliability.

This high performance SPP/EPP/ECP parallel card adds 1 DB25 parallel port, perfect for connecting printers, scanners, CD-R/RW drives, memory card readers, bar code scanners and more. With the added convenience of plug-and-play capability, installing the parallel adapter card is hassle-free! The PCIe Parallel card also includes both standard and half-height/low profile mounting brackets for compatibility with almost any system form factor.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Connects any parallel-based peripheral to your PC, including printers, scanners, CD-R/RWs, Zip® drives, and memory card readers

Features

- SPP/EPP/ECP Parallel port fully supports existing Centronics interface
- Packaged with low profile/half-height bracket attached, includes full profile bracket
- Compliant with PCI Express Base Specification 1.1a
- Compliant with PCI Power Management 1.2

Technical Specifications

Warranty	2 Years
Bus Type	PCI Express
Card Type	Low Profile (SP bracket incl.)
Chipset ID	PLX/Oxford - OXPCle952
Interface	Parallel
Port Style	Integrated on Card
Ports	1
Maximum Data Transfer Rate	Up to 2.5Mbps
Connector Type(s)	1 - PCI Express x1 Male
External Ports	1 - DB-25 (25 pin; D-Sub) Female
OS Compatibility	Windows® 8 / 8.1 (32/64bit), 7 (32/64), Vista (32/64), XP (32/64), 2000, 98SE, 95, XP Embedded, CE 6.0 / 5.0 Windows Server® 2012, 2008 R2, 2003, 2000 Linux 2.4.x / 2.6.x
Product Height	4.7 in [120 mm]
Product Length	0.8 in [21 mm]
Product Weight	2.3 oz [65 g]
Product Width	4.3 in [110 mm]
Humidity	5~85% RH
Operating Temperature	0°C 50°C (32°F to 122°F)
Storage Temperature	-20°C 60°C (-4°F to 140°F)
Shipping (Package) Weight	4.2 oz [120 g]
Included in Package	1 - Low profile PCI Express Parallel Card
Included in Package	1 - Full Profile Bracket
Included in Package	1 - Driver CD
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility

