

3 Port HDMI® Auto Switch w/ IR Remote Control

StarTech ID: VS123HD



The VS123HD 3-port HDMI® Auto Switch features three prioritized HDMI input ports. If the active HDMI source is turned off, disconnected, or otherwise lost, the switch automatically selects the next available HDMI signal as the priority output, ensuring the display is always receiving a signal.

The automatic switch includes an IR Remote Control, so you'll be able to share an HD projector or display between three HDMI audio/video sources, with the option to manually control the switch from a distance or through the easy-to-use front panel toggle button.

Ideal for High-Definition applications, this 3-in/1-out HDMI switch supports true High-Definition 1080p resolutions (WUXGA/1920x1200 from PC/computer) as well as 7.1 Surround Sound audio, ensuring the best possible multimedia experience from connected devices.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Switching between High-Definition audio-video devices e.g Blu-ray players, satellite receivers, video game consoles or computers with HDMI output
- Digital signage scenarios that require a signal always be available to a display

Features

- Transparent, automatic HDMI switching
- IR remote control
- Built-in HDMI display cable saves you from purchasing an additional cable
- Supports HDTV resolutions up to 1080p
- Supports PC resolutions up to 1920x1200
- Easy installation and set up in minutes
- Allows for cables up to 30ft (10m) in length
- Supports High Speed HDMI device switching
- HDCP Compliant
- Supports 3D Video

Technical Specifications

Warranty 2 Years

Color Black

Enclosure Type Plastic

Product Height 1 in [25 mm]

Product Length 3.2 in [81 mm]

Product Weight 3.5 oz [99.5 g]

Product Width 2.2 in [55 mm]

Audio Yes

Industry Standards High Speed HDMI®, HDCP

Output Signal HDMI

Ports 3

Max Distance 10 m / 33 ft

Maximum Resolutions 1920x1200

Digital Resolutions

Wide Screen Supported Yes

Connector A 1 - HDMI (19 pin) Male

Connector B 3 - HDMI (19 pin) Female

Note Port 1 is set to have higher priority than port 2 or port 3 when all signals are on. Port 2 is set to have higher priority than port 3 when both signals are on, but Port 1 is off.

LED Indicators 3 - Two Green for Display Status, and one red for power.

Humidity 10% to 85%RH

Operating Temperature 0°C to 70°C (32°F to 158°F)

Storage Temperature -65°C to 150°C (-85°F to 302°F)

Shipping (Package) Weight 6.3 oz [178.2 g]

Included in Package 1 - 3 Port High Speed HDMI® Auto Switch

Included in Package 1 - Remote Control

Included in Package 1 - IR Extender Cable

Included in Package 1 - Instruction Manual

Certifications, Reports and Compatibility

