

1U 17" Rackmount LCD Console with 8 Port Multi-Platform KVM

StarTech ID: RACKCONS1708



This 1U Folding Rackmount LCD Console offers a high quality KVM solution, featuring a 17in LCD display, full-size (106 key) keyboard and mouse touchpad, as well as an 8-port KVM module.

A cost-effective KVM control solution, the integrated module can be cascaded with up to 8 more 8-port KVM switches, for control of up to 64 computers from this single module. The module supports both USB and PS/2 controlled computers, and offers multi-platform KVM control, supporting PC, Mac and Sun servers and systems to ensure broad compatibility.

The LCD Rack Console is able to work with virtually any existing KVM switch and any standard rack or cabinet that is 30in or greater in depth.

Applications

- Centralized control of up to 64 PCs
- Improving the internal space efficiency of existing cabinets
- Managing cabinet mounted servers
- User can complete the basic tasks in the server room



Features

- On Screen Display (OSD)
- Durable design
- Compatible with PC, Mac and Sun servers and systems
- Cascadable design
- Hot-pluggable
- Security features, including port locking and auto scan
- Login authentication restricts access to authorized users
- Universal 8 port KVM switch Module controls up to 8 computers directly and up to 64 computers by cascading 8 additional KVM switches
- Supports PCs with USB or PS/2 keyboard and mouse connectors
- Auto Scan Mode lets you switch between computers for easy monitoring



Technical Specifications

Warranty 2 Years

Audio No
Daisy-Chain Yes
Display Size 17in
Key Lock Yes
KVM Ports 8
Multi-Monitor No

Panel Type Active Matrix TFT LCD

PC Interface USB and PS/2

PC Video Type VGA Rack-Mountable Yes

Aspect Ratio Standard (4:3)
Brightness 250 cd/m²
Contrast Ratio 1000:1
IP Control No

Maximum Analog Resolutions 1280X1024 (SXGA)

Maximum Cascaded Computers 64
Maximum Number of Users 1

MTBF 60,000 Hours
Pixel Pitch Support 0.264 x 0.264 mm

Port Selection Support Hotkeys and OSD (On Screen Display)

Response Time 5ms

Viewing Angle 170° (H), 160° (V)

Console Interface(s) 1 - VGA (15 pin; High Density D-Sub) Female

Console Interface(s) 2 - PS/2 (6 pin; Mini-DIN) Female

Host Connectors 8 - VGA (15 pin; High Density D-Sub) Female
OS Compatibility OS independent; No software or drivers required

Color Black

Enclosure Type Heavy Duty Steel

Maximum Mounting Depth 31.6 in [802 mm]

Minimum Mounting Depth 25.8 in [655 mm]

Product Height 1.8 in [45 mm]

Product Length 24.9 in [633 mm]



Hard-to-find made easy®

Spec Sheet

Product Weight	24.3 lb [11 kg]
Product Width	19 in [483 mm]

Output Current 4A
Output Voltage 12 DC

Power Source AC Adapter Included

Humidity 10~90% RH

Operating Temperature 0°C to 50°C (32°F to 122°F)
Storage Temperature -20°C to 60°C (-4°F to 140°F)

Shipping (Package) Weight 44.5 lb [20.1 kg]

Included in Package 1 - 1U LCD Rack Console Drawer

Included in Package 1 - 1U 8 Port Multi-Platform KVM Switch

Included in Package 1 - Mounting Rails (Set)

Included in Package 1 - Power Adapter

Included in Package 1 - Instruction Manual

Certifications, Reports and Compatibility







