

2 Port USB HDMI® KVM Switch with Audio and USB 2.0 Hub

StarTech ID: SV231HDMIUA





The SV231HDMIUA 2-port USB HDMI® KVM Switch lets you control two USB-enabled multimedia computers or devices with HDMI video interfaces, using a single peripheral set/console (USB keyboard, mouse, monitor, speakers and microphone).

A highly versatile KVM solution, the USB HDMI KVM Switch features an integrated 2-port USB 2.0 hub that lets selected computers access shared high speed USB devices, eliminating the cost of duplicate USB peripheral purchases.

Ensuring high quality video capability, the HDMI KVM switch supports HD resolutions of up to 1920 x 1200. Offering genuine digital signal transmission over the cable, this switch can be used to share one HD panel between multiple HDMI sources such as Blu-Ray players, Video Game consoles and HD media centers.

The switch also supports audio and microphone switching functions and allows you to select connected computers, USB device hub ports and audio/mic channels either simultaneously or independently using either front-panel push-buttons or keyboard hotkeys.






Keyboard / Mouse

Share your keyboard, mouse, external storage between your PC and game console.

Configuration for: Graphic designers, programmers, stock trading, financial applications



Backed by a StarTech.com 3-year warranty and free lifetime technical support.

Applications

- Ideal for sharing two newer HDMI® multimedia PCs with an HDMI monitor
- Students can use a single monitor and connect their gaming console along side their PC or laptop
- Allows multimedia PCs to share peripherals and a single high definition television
- Use in the Office to connect two multimedia PCs to a single console connection increasing productivity

Features

- Supports push button and hotkey PC Switching
- Integrated USB 2.0 hub - Share USB peripherals between PCs
- Supports High Resolutions Digital video up to UXGA (1600x1200), WUXGA (1920x1200), and 1080p (1920x1080)
- No software drivers required; OS independent
- Supports Plug&Play operation
- Supports both HDMI® audio and 3.5mm analog audio
- Independent Audio switching
- Audible tone to indicate PC switching
- User-defined scan time intervals
- Manual video adjustments via rear function button

Technical Specifications

Warranty	3 Years
Color	Black
Enclosure Type	Steel
Product Depth	2.8 in [70 mm]
Product Height	1.6 in [40 mm]
Product Weight	28.2 oz [800 g]
Product Width	4.9 in [124.8 mm]
Audio	Yes
Cables Included	No
Daisy-Chain	No
KVM Ports	2
Multi-Monitor	No
PC Interface	USB
PC Video Type	HDMI
Rack-Mountable	No
IP Control	No
Maximum Digital Resolutions	1920 x 1200
Maximum Number of Users	1
Port Selection Support	Push Button and Hotkeys
Wide Screen Supported	Yes
Console Interface(s)	1 - HDMI (19 pin) Female
Console Interface(s)	2 - 3.5 mm Mini-Jack (3 Position) Female
Console Interface(s)	4 - USB A (4 pin) Female
Host Connectors	2 - HDMI (19 pin) Female
Host Connectors	2 - USB B (4 pin) Female
Host Connectors	4 - 3.5 mm Mini-Jack (3 Position) Female
OS Compatibility	OS independent; No software or drivers required
LED Indicators	2 - Online/Active (Green - Connected PC is online, Red - PC is selected)
Center Tip Polarity	Positive
Input Current	0.8A
Input Voltage	110 ~ 240 AC
Output Current	1.5A
Output Voltage	12 DC

Plug Type	M
Power Source	AC Adapter Included
Humidity	0~80% RH
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Shipping (Package) Weight	2.5 lb [1.1 kg]
Included in Package	1 - 2 Port HDMI KVM
Included in Package	1 - Package of Rubber feet
Included in Package	1 - Power Adapter
Included in Package	1 - User Manual

Certifications, Reports and Compatibility

