

## HDMI to DisplayPort Converter - 4K

StarTech ID: HD2DP



This HDMI® to DisplayPort™ converter lets you connect an HDMI enabled video source, such as a Blu-ray™ player, camera, video game console or computer, to a DisplayPort monitor or projector.

The compact adapter is USB-powered and supports video resolutions up to 4K, giving you the freedom to connect your 4K HDMI equipped Ultrabook™ or laptop to an Ultra HD DisplayPort projector. It's the perfect solution for a variety of settings, including office boardrooms or trade shows.

### Save money and hassle

This HDMI to DisplayPort converter can save you time and money. It works seamlessly with your existing setup when connecting a new source or display, eliminating cost by ensuring that you won't need to change or upgrade your main components.

The HDMI to DP adapter offers plug-and-play installation, providing a hassle-free setup with no software or drivers to install. Plus, the adapter features a compact design that blends seamlessly with your workstation or entertainment center.

### Be more productive

Using the HDMI to DisplayPort adapter, you can connect a secondary monitor to your laptop. Having the extra display offers a definite productivity boost because the added screen space means you can work more efficiently by multitasking more easily, and accomplish more in the same amount of time. It's perfect for office use where you'll often view documents, spreadsheets, and web pages across multiple screens.

### Enjoy Ultra HD picture quality

At four times the resolution of high-definition 1080p, you'll be amazed at the picture quality of a 4K monitor or television. This HDMI to DisplayPort (DP) converter lets you deliver high-resolution content to your DP enabled

display, through the astonishing quality of Ultra HD. Plus, the adapter is backward compatible with 1080p displays, which makes it a great accessory for home, office or other workspace applications. Support for 4K makes the adapter great for video production applications such as viewing and editing post-production video or viewing camera footage from an HDMI source on your DisplayPort monitor.

The HD2DP is backed by a StarTech.com 2-year warranty and free lifetime technical support.

### **Applications**

- Present content from your HDMI equipped computer on a DisplayPort monitor
- View documents, spreadsheets, and web pages across multiple screens
- Design and edit graphic files on your DP display using the HDMI output on your computer
- Capture 4K video content from an HDMI source and view it on a DisplayPort monitor
- Edit and view post-production video on a 4K display
- Viewing camera footage from your HDMI source on a DisplayPort monitor

### **Features**

- Integrates seamlessly in your setup, with a compact design and plug-and-play installation
- Increases your productivity by using your HDMI output to connect another display for multi-tasking
- Astonishing picture quality with support for video resolutions up to Ultra HD 4K
- Backward compatible with high-definition displays supporting 1920x1200 and 1080p resolutions
- No power adapter, software or drivers required

Technical Specifications

|                             |   |
|-----------------------------|---|
| Warranty                    | 2 Years   |
| Color                       | Black   |
| Product Height              | 0.5 in [13 mm]  |
| Product Length              | 8.7 in [220 mm]   |
| Product Weight              | 1.3 oz [36 g]   |
| Product Width               | 0.9 in [23 mm]  |
| Adapter Style               | Adapter   |
| Audio                       | Yes   |
| Chipset ID                  | STDP2600  |
| Output Signal               | DisplayPort   |
| Audio Specifications        | 7.1 surround sound  |
| Maximum Digital Resolutions | 4K  |
| Supported Resolutions       | 4k x 2K (Ultra HD)<br>1920x1200<br>1920x1080 (1080p)<br>1280x720 (720p) |
| Wide Screen Supported       | Yes   |
| Connector A                 | 1 - HDMI (19 pin) Male Input  |
| Connector B                 | 1 - DisplayPort (20 pin) Female Output                                  |
| Humidity                    | 20~95% RH non-condensing  |
| Operating Temperature       | -20°C to 85°C (-4°F to 185°F)   |
| Storage Temperature         | -20°C to 85°C (-4°F to 185°F)   |
| Shipping (Package) Weight   | 5 oz [141 g]  |
| Included in Package         | 1 - HDMI to DisplayPort adapter   |
| Included in Package         | 1 - USB extension cable   |

Certifications, Reports and Compatibility

