

# 19in 1U Rackmount 8 Outlet PDU Power Distribution Unit 125V 15A (12A UL)

StarTech ID: RKPW081915



This 8-outlet (120V 15A)(12A UL) Rack PDU delivers a cost-effective power distribution solution for your server rack/cabinet. The 1U PDU can be mounted horizontally in any server rack 19" in depth or greater, to provide eight 120V 15A power ports/outlets, and features a rugged steel casing to ensure maximum durability.

The front of the PDU features two LEDs to indicate proper ground and surge detection while enabling you to control the power state with an illuminated power/reset switch.

To prevent costly breakdowns of connected devices, the rackmount PDU features a built-in circuit breaker and reset switch, ensuring dependable performance of vital equipment.

# **Applications**

- 8 easily accessible power outlets in a compact 1U of rack space
- Localize the power control for all of your connected system

#### **Features**

- Solid Steel Chassis for durability
- Integrated 6ft power cord
- · LED indicators for ground and surge detection
- Illuminated reset and power switch
- Meets ANSI/EIA RS-310-D standards
- Built in circuit breaker



## **Technical Specifications**

Warranty 2 Years
Load Capacity 1800 VA
Maximum Input Current per Phase 15A
Maximum Output Voltage 125V
Maximum Total Current Draw per Phase 15A
Nominal Input Voltage 120V
Nominal Output Voltage 120V
Regulatory Derated Input Current (North America) 12A

Output Connectors 8 - NEMA 5-15 Power (North America) Receptacle

Cable Length 6 ft [1.8 m]

Color Black Enclosure Type Steel

Product Height 1.7 in [4.3 cm]
Product Length 19 in [48.3 cm]
Product Weight 4.5 lb [2 kg]
Product Width 3.8 in [9.6 cm]
LED Indicators 1 - Ground

LED Indicators 1 - Surge
Humidity 0% RH

Operating Temperature -5°C to 45°C (23°F to 113°F)
Storage Temperature -25°C to 65°C (-13°F to 149°F)

Shipping (Package) Weight 4.9 lb [2.2 kg]

Included in Package 1 - 8 Port Power Distribution Unit

Included in Package 1 - Installation Document

## Certifications, Reports and Compatibility



