

USB 2.0 to SATA/IDE Combo Adapter for 2.5/3.5" SSD/HDD

StarTech ID: *USB2SATAIDE*



This USB 2.0 to IDE/SATA Adapter Cable connects any standard 2.5in or 3.5in SATA or IDE hard drive to a computer through USB 2.0. The adapter lets you connect a bare drive with no enclosure, saving time and hassle.

The USB 2.0 SATA/IDE Adapter features LED indicators that allow you to easily monitor status and activity updates, and is designed for durability and reliability.

Applications

- Service technicians who need to test or retrieve data from old hard drives
- Technicians who travel and deal with many different types of hard drives
- Connect your 2.5" and 3.5" drives to almost any notebook or desktop
- Ideal for testing and quickly swapping drives

Features

- Built in connectors for both 2.5in and 3.5in SATA and IDE hard drives
- LED indicators provide status and activity updates
- High Speed USB 2.0 host interface, with support for transfer rates up to 480 Mbps
- Compact, portable form factor

Technical Specifications

Warranty	2 Years
Chipset ID	JMicron - JM20337
Compatible Drive Types (Type and Rate)	SATA & IDE
Drive Size	2.5in & 3.5in
Maximum Data Transfer Rate	480 Mbps
Type and Rate	USB 2.0 - 480 Mbit/s
Drive Connectors	1 - IDE (40 Pin; EIDE/PATA) Female
Drive Connectors	1 - IDE (44 Pin; EIDE/PATA; 2.5" HDD) Female
Drive Connectors	1 - LP4 (4 pin; Molex Large Drive Power) Female
Drive Connectors	1 - SATA (7 pin; Data) Plug
Drive Connectors	1 - SATA Power (15 pin) Receptacle
Host Connectors	1 - USB A (4 pin) Male
OS Compatibility	Windows® 8/8.1 (32/64bit), 7 (32/64bit), Server 2008 (32/64), Vista(32/64), Server 2003 (32/64) XP(32/64), 2000 Apple® Mavericks (10.9) OSX Mountain Lion (10.8), Lion (10.7), Snow Leopard (10.6) Linux
Note	Backwards compatible with USB 1.1 standard, but not recommended due to slow transfer rate. Maximum supported drive size in Mac OSX® is 2TB
Color	Black
Enclosure Type	Plastic
Product Height	0.6 in [15 mm]
Product Length	2.8 in [70 mm]
Product Weight	1.9 oz [54 g]
Product Width	1.7 in [43 mm]
LED Indicators	1 - IDE Detect/Activity
LED Indicators	1 - SATA Detect/Activity
LED Indicators	1 - USB Link
Input Current	1A
Input Voltage	110 ~ 240 AC
Output Current	2A

Output Voltage	12/5 DC
Plug Type	Custom
Power Source	AC Adapter Included
Shipping (Package) Weight	16.1 oz [456 g]
Included in Package	1 - USB to SATA/IDE converter
Included in Package	1 - SATA Cable
Included in Package	1 - AC Power Cord
Included in Package	1 - Power Supply
Included in Package	1 - Driver CD
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility

