

Key **Features**

SuperClear MVA Panel Technology | High-definition Daisy
Chain Capability | Versatile Connectivity | Ergonomic Design |
Optimized View Settings



Product **Description**

With future-proof connectivity and advanced ergonomics, the ViewSonic® VG2249 is a productivity-boosting monitor perfect for corporate, government, and education environments. Designed with both a DisplayPort input and output, this monitor delivers easy, single-cable daisy-chaining of multiple monitors for increased productivity. With SuperClear® MVA panel technology for wide-angle viewing, and a 20M:1 dynamic contrast ratio, incredibly sharp images and vivid color remain consistent across multiple daisy-chained screens. For maximum comfort and a customized fit, a robust fully ergonomic stand gives you tilt, pivot, swivel, and height-adjustable options. Additional connectivity options include VGA, HDMI, and Mini DisplayPort so that you can connect to a variety of high-definition and analog devices – today and tomorrow.









a call: 888.881.8781

Contact Sales — email: salesinfo@viewsonic.com

visit: viewsonic.com

Display:		Video Signal:		Awards:
Type:	MVA	Frequency Horizontal:	Analog: 24 ~ 82KHz. Digital: 15 ~ 82KHz	ND/2
Colors:	16.7M	Frequency Vertical:	Analog: 50 ~ 75Hz. Digital: 50 ~ 75Hz	PC .
Static Contrast Ratio:	3000:1	Video Input:		Cholos
Viewing Angles:	178° horizontal, 178° vertical	Analog Sync:	Separate Sync / Composite Sync / Sync on Green	
Resolution:	1920 x 1080	Digital Sync:	TMDS, PCI-E	
Viewable Area (in.):	21.5	Ergonomics:		
Dynamic Contrast Ratio:	20M:1	Height Adjust (mm):	135	
Backlight Life (Hours):	40,000	Swivel:	360°	
Response Time (GTG):	5ms	Pivot:	90°	
Light Source:	WLED	Tilt (Forward/Back):	Forward 6° / Back 25°	
Brightness:	250 cd/m2	Weight (imperial):		
Panel Surface:	Anti-glare, Hard coating (3H)	Net (lbs):	10	
Aspect Ratio:	16:9	Net Without Stand (lbs):	6.7	
Display Size (in.):	22	Gross (lbs):	13.5	
Compatibility:		Weight (metric):		
PC Resolution (max):	1920 x 1080	Net (kg):	4.5	
Connector:		Net Without Stand (kg):	3.0	
), VGA(1), HDMI 1.4(1), Display Port(1), Display Port	Gross (kg):	6.1	
Out(1), Mini Display Port(1)		Dimensions (imperial) (WxHxD):		
Audio: Internal Speakers:	2W (x2)	Packaging (in.):	22.8 x 19 x 7.1	
Power:	ZW (XZ)	Physical (in.):	20.2 x 16.5 x 9.4	
Eco Mode (Conserve):	12W	Physical Without Stand (in.):	20.2 x 12 x 2.1	
Eco Mode (optimized):	14W	Dimensions (metric) (WxHxD):		
Consumption (typical):	19W	Packaging (mm):	578 x 482 x 180	
Consumption (max):	44W	Physical (mm):	512 x 418 x 240	
	AC 100-240V (universal), 50-60Hz	Physical Without Stand (mm):	512 x 304 x 54	
Voltage:		General:		
Stand-by:	.5W	Regulations: cULus, FCC, ICES003, Energy Star 7.0, EPEAT Gold, UL-MX-CoC, Mexico		
Additional Hardware: Kensington Lock Slot:	1	Energy		
Controls:	1	PACKAGE CONTENTS: LCD Display, Power Cable (1.8m), Mini DP to DP Cable (1.8m), USB3.0 Upstream Cable (1.5m), Quick Start Guide, ViewSonic Wizard CD-ROM		
Physical Controls:	1,2, Up, Down, Power	Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.		
,	Auto Image Adjust, Contrast/Brightness, Input	Warranty: Three-year limited warranty on parts, labor and backlight		
On Screen Display:	Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for	UPC: 766907853414		
		Accessories:		
Operating Conditions	complete OSD functionality)	CB-00008948, CB-00010555, CB-00010684, CB-00010958, LCD-CABLE-001, LCD-WMK-		
Operating Conditions: Temperature:	32-104° F (0-40° C)	001, VSPF2150, cb-00011486		
Humidity (non-condensing):	20-90%			
Mount:	20°2070			
VESA Compatible:	100 x 100 mm			
123/1 Computations.	. 55 X 100 IIIII			