

Key **Features**

Resistive Touch Technology | Versatile Connectivity | MEGA

Dynamic Contrast Ratio | Dual Integrated Speakers



Product **Description**

The TD2210 is a 22" (21.5" viewable) Full HD monitor with resistive touch technology. With a robust, pressure-sensing touchscreen that is resistant to screen contamination, the TD2210 is ideal for use in retail, POS, and commercial environments. Resistive touch technology on the TD2210 is also fully functional in gloved environments and compatible with styluses. Featuring stunning Full HD resolution and 20M:1 MEGA Dynamic Contrast Ratio, the TD2210 delivers extremely sharp and crisp images. Flexible connectivity options include VGA, DVI, and USB ports, and a VESA-mountable design offers additional convenience for use as a wall-mounted display. Industry-leading warranty protection and ViewSonic product quality makes this durable touch display a great long-term investment for a variety of environments.









a call: 888.881.8781

Contact Sales — email: salesinfo@viewsonic.com

visit: viewsonic.com

Display:		Operating Conditions:	
Type:	TN	Temperature:	32-104° F (0-40° C)
Colors:	16.7M	Humidity (non-condensing):	20-90%
Static Contrast Ratio:	1000:1	Ergonomics:	
Viewing Angles:	170° horizontal, 160° vertical	Tilt (Forward/Back):	5°/20°
Resolution:	1920 x 1080	Additional Hardware:	
Viewable Area (in.):	21.5	Kensington Lock Slot:	1
Dynamic Contrast Ratio:	20M:1	Mount:	
Backlight Life (Hours):	40,000	VESA Compatible:	100 x 100 mm
Response Time (GTG):	5ms	Weight (metric):	
Light Source:	WLED	Gross (kg):	6.5
Brightness:	350 cd/m2	Net (kg):	4.8
Panel Surface:	3H Scratch Resistant Surface Hardness	Net Without Stand (kg):	3.9
Aspect Ratio:	16:9	Weight (imperial):	
Display Size (in.):	22	Net (lbs):	10.5
Compatibility:	22	Net Without Stand (lbs):	8.7
PC Resolution (max):	1920 x 1080	Gross (lbs):	14.4
Touch:		Dimensions (metric) (WxHxD):	
Technology:	Resistive	Packaging (mm):	570 x 427 x 214
Touch Points:	2	Physical (mm):	512 x 364 x 240
Connector:		Physical Without Stand (mm):	512 x 311 x 64
USB 2.0 Type A(1), USB 2.0 Type B(1), VGA(1), DVI-I(1)		Dimensions (imperial) (WxHxD):	
Audio:		Packaging (in.):	22.4 x 16.8 x 8.4
Internal Speakers:	2W (x2)	Physical (in.):	20.1 x 14.3 x 9.5
Video Signal:		Physical Without Stand (in.):	20.1 x 12.2 x 2.5
Frequency Horizontal:	24 ~ 83KHz	General:	
Frequency Vertical:	50 ~ 76Hz	Regulations: cULus, FCC-B, ICES003, Energy Star 7.0, EPEAT Silver, UL-MX-CoC, Mexico Energy	
Analog Sync:	Separate Sync / Composite Sync / Sync on Green	PACKAGE CONTENTS: LCD Display Power Cable (1.8m) VGA Cable (1.8m) DVI Cable (1.8m) USB2.0 Cable (1.8m) Audio Cable (1.8m) Quick Start Guide ViewSonic Wizard CD-ROM	
Power:		Warranty: Three-year limited warranty on parts, labor and backlight	
Eco Mode (Conserve):	11.5W		
Eco Mode (optimized):	14W	Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.	
Consumption (typical):	17.5W	UPC: 766907856217	
Consumption (max):	29.5W	Accessories: CB-00008187, LCD-CABLE-001, LCD-WMK-001, VSPF2150, cb-00011486	
Voltage:	AC 100-240V (universal), 50-60Hz	Awards:	
Stand-by:	0.5W	Awards:	
Controls:		PE	
Physical Controls:	GameMode, 1, 2, 3, 4, Power		
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)		