

Key Features


Amazing color accuracy | Secure MHL/HDMI port | Network capable | Smart design | Enhanced sound



Product Description

The ViewSonic LightStream™ PJD6352 networkable projector features 3,500 lumens, native XGA 1024x768 resolution, and an intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment, while SonicExpert™, ViewSonic's proprietary sound enhancement technology, powers a 10W speaker to deliver incredibly clear and audible sound. PortAll, a neatly designed and enclosed HDMI/MHL connection compartment, supports streaming media from wireless HDMI dongles or MHL connectors, while a cable management hood connects onto the back of the projector and eliminates unsightly cable clutter. With HV keystone, corner adjustment, 1.3x optical zoom, and easy network management, the PJD6352 provides flexible setup. Designed with smarter features and extensive connectivity, the networkable PJD6352 is ideal for use in education and corporate environments.






1024 x 768
RESOLUTION



3,500
LUMENS



1.51-1.97
THROW RATIO

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Throw Distance:	3.28 – 32.8 ft. / 1.0 – 10.0 m
Throw Ratio:	1.51-1.97
Type:	DLP
Lens:	1.3x Manual optical zoom / manual optical focus
Keystone:	Vertical (± 30°) / Horizontal (± 30°)
Light Source (watt):	210
Light Source Life, Normal (hours):	4000
Light Source Life, Dynamic Eco-Mode (hours):	10000
Brightness (ANSI Lumens):	3,500
Color Depth:	30 bits, 1.07B Color (10+10+10)
Resolution:	1024 x 768
Aspect Ratio:	4:3 (native)
Resolution Type:	XGA
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m

Video Signal:

Frequency Horizontal:	15–102KHz
Frequency Vertical:	23–120Hz

Compatibility:

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080

Connector:

Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1), 3.5mm Audio In(2), HDMI(1), HDMI 1.4(1), HDMI MHL(1), Composite RCA Video In(1), S-Video In(1), Mini USB(1)

Audio:

Internal Speakers:	10W
--------------------	-----

Power:

Voltage:	100~240VAC (Auto Switching), 50-60Hz (universal)
Consumption (max):	330W
Stand-by:	<0.5W

Controls:

Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Picture, Source, System Setup (Basic),

Weight (imperial):

Net Without Stand (lbs):	5.07
Gross (lbs):	8.82

Weight (metric):

Net Without Stand (kg):	2.3
Gross (kg):	4.0

Dimensions (metric) (WxHxD):

Packaging (mm):	410 x 450 x 225
Physical Without Stand (mm):	316 x 103.7 x 228

Dimensions (imperial) (WxHxD):

Packaging (in.):	16.0 x 17.72 x 8.85
Physical Without Stand (in.):	12.44 x 4.08 x 8.98

General:

Regulations: CB, TUV-GS, UL/cUL, FCC (including ICES-003), CE, C-Tick Mexico Energy test/Registration, EAC, UkrSEPRO/ EMC DOC, UL COC, TUV-S Mark (Argentina), PSB, KCC, KC, SASO, CCC, WEEE, RoHS, REACH, SVHC, ErP

PACKAGE CONTENTS: PJD6352 projector, power cable, VGA cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide), cable management

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service**

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907780819

Accessories:

Operating Conditions:

Temperature:	32-104° F (0-40° C)
Humidity (non-condensing):	10-90%

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---