
## Key **Features**

Two Monitors in a Single Package | SuperClear MVA Panel
Technology | High-definition Daisy Chain Capability |
Versatile Connectivity | Optimized View Settings



# Product **Description**

If you're looking for high-performance monitors with easy deployment and mounting capabilities, look no further than the ViewSonic® VG2449\_H2. Sold as a dual pack of monitors without monitor stands, the VG2449\_H2 requires less packaging for a reduced environmental footprint, while still providing VESA-compatible mounting for easy dual-screen installation. With future-proof connectivity and advanced ergonomics, the ViewSonic® VG2449\_H2 is a productivity-boosting monitor perfect for corporate, government, and education environments. Designed with both a DisplayPort input and output, these monitors deliver easy, single-cable daisy-chaining for increased productivity. With SuperClear® MVA panel technology for wide-angle viewing, and a 20M:1 dynamic contrast ratio, incredibly sharp images and vivid color remain consistent across multiple daisy-chained screens. Additional connectivity options include VGA, HDMI, and Mini DisplayPort so that you can connect to a variety of high-definition and analog devices – today and tomorrow.



- 1. Menu Control Panel
- 2. VESA Compatible Wall Mount (100 x 100 mm)
- 3. Kensington Lock Slot
- 4. AC In
- 5. HDMI
- 6. DisplayPort In
- 7. Mini DisplayPort In



- 8. VGA
- 9. Internal Speakers
- 10. USB Type B
- 11. USB 3.0 (x2)

- 12. Headphones
- 13. Audio In
- 14. DisplayPort Out







all: 888.881.8781

**Contact Sales** — email: salesinfo@viewsonic.com

visit: viewsonic.com

Display:	
Display Size (in.):	24
Viewable Area (in.):	23.6
Type:	MVA
Resolution:	1920 x 1080
Static Contrast Ratio:	3000:1
Dynamic Contrast Ratio:	20,000,000:1
Light Source:	WLED
Brightness:	250 cd/m2
Colors:	16.7M
Color Space Support:	6-bit+FRC
Aspect Ratio:	16:9
Response Time (Typical GTG):	22ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	40,000
Panel Surface:	Anti-glare, Hard coating (3H)
Compatibility:	
PC Resolution (max):	1920 x 1080
Connector:	
USB 3.0 Type A(2), USB 3.0 Type B(1), 3.5mm Audio In(1), 3.5mm Audio Out(1), VGA(1), HDMI 1.4(1), Display Port(1), Display Port Out(1), Mini Display Port(1)	
Audio:	
Internal Speakers:	2W (x2)
Power:	
Eco Mode (Conserve):	14W
Eco Mode (optimized):	16W
Consumption (typical):	20W
Consumption (max):	46W
Voltage:	AC 100-240V (universal), 50-60Hz
Stand-by:	0.5W
Additional Hardware:	
Kensington Lock Slot:	1
Controls:	
Physical Controls:	1,2, Up, Down, Power
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input

## Video Signal:

Frequency Horizontal:	15 ~ 82KHz
Frequency Vertical:	50 ~ 75Hz

## **Video Input:**

Digital Sync:	TMDS, PCI-E
---------------	-------------

## Weight (imperial):

Net (lbs):	15.88
Gross (lbs):	18 14

#### Weight (metric):

Net (kg):	7.22
Gross (kg):	9.9

#### Dimensions (imperial) (WxHxD):

Packaging (in.):	25.47 x 16.65 x 10.31
Physical (in.):	22.06 x 13.10 x 2.33

## Dimensions (metric) (WxHxD):

Packaging (mm):	647 x 423 x 262
Physical (mm):	560.28 x 332.72 x 59.18

#### General:

Regulations: cULus, FCC, ICES003, Energy Star 7.0, EPEAT Gold, UL-MX-CoC, Mexico Energy

PACKAGE CONTENTS: Power Cable (1.8m)  $\times$  2, Mini DP to DP Cable (1.8m)  $\times$  2, USB3.0 Upstream Cable (1.8m)  $\times$  2, Quick Start Guide  $\times$  1

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907890136

#### **Accessories:**

Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

## **Operating Conditions:**

Temperature: 32-104° F (0-40° C)

Humidity (non-condensing): 20-90%

Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (03/08/2017 10:26 AM PST)