


Key **Features**

Seamless Viewing Experience | WQHD Resolution | Loaded with Connectivity | Ultimate Color Accuracy | Excellent Screen Uniformity



Product **Description**

Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP2771 WQHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel and a sleek frameless design, the VP2771 provides a near-seamless viewing experience ideal for multi-monitor setups. For simple, single-cable daisy chaining of multiple monitors, the VP2771 is equipped with future-proof DisplayPort technology, in addition to MHL 2.0 and USB 3.1 type C ports. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E≤2 value for superior color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Add to that 6-axis color adjustment functionality, and this monitor provides the ultimate color processing capability for professional applications. What's more, productivity-boosting features include an advanced ergonomic design, a built-in ambient light sensor, and a KVM switch. Hardware calibration is also available with the optional ViewSonic Colorbration Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, content creation, and other color-critical applications.



4. USB 3.1 Type A (x3)

- 1. Menu Controls
- 2. VESA Compatible Wall Mount



- 8. DisplayPort Out
- 9. Headphones

12. DisplayPort In

100 x 100 mm 3. HDMI/MHL **6. U\$B** ∄yp∉y&pe C 7. Kensington Lock Slot 10. DC In 11. Mini DisplayPort In





PANEL





Display:		Ergonomics:	
Туре:	IPS	Height Adjust (mm):	130
Static Contrast Ratio:	1000:1	Swivel:	120°
Viewing Angles:	178° horizontal, 178° vertical	Pivot:	900
Resolution:	2560 x 1440	Tilt (Forward/Back):	5°/21°
Viewable Area (in.):	27	Weight (imperial):	
Dynamic Contrast Ratio:	20M:1	Net (lbs):	15
Backlight Life (Hours):	30,000	Net Without Stand (lbs):	9.6
Response Time (GTG):	5ms	Gross (lbs):	23
Light Source:	WLED	Weight (metric):	
Brightness:	350 cd/m2	Net (kg):	6.8
Panel Surface:	Anti-glare, hard-coating (3H)	Net Without Stand (kg):	4.3
Aspect Ratio:	16:9	Gross (kg):	10.6
Display Size (in.):	27	Dimensions (imperial) (WxHxD):	
Compatibility:		Packaging (in.):	28.3 x 10.6 x 18.1
PC Resolution (max):	2560 x 1440	Physical (in.):	24.2 x 22 x 8.5
Connector:		Physical Without Stand (in.):	24.2 x 14.3 x 2.1
USB 3.1 Type A(3), USB 3.1 Type B(1), USB 3.1 Type C(1), 3.5mm Audio Out(1), HDMI MHL(1), Display Port(1), Display Port Out(1), Mini Display Port(1)		Dimensions (metric) (WxHxD): Packaging (mm):	720 x 268 x 460
Power:		Physical (mm):	613 x 546 x 216
Voltage:	AC 100-240V (universal), 50-60Hz	Physical Without Stand (mm):	613 x 364 x 52
Stand-by:	0.3W	General:	
Additional Hardware:			, REACH, UL,cUL,FCC-B,Mexico CoC,EPEAT
Kensington Lock Slot:	1	GOLD,Energy Star	
Controls: Physical Controls:	1, 2, 3, 4, 5, Power	PACKAGE CONTENTS: LCD Display AC/DC Adapter Power Cable(cable length :1.8M) Mini DP to DisplayPort Cable (cable length :1.8M) USB3.0 Up Stream Cable(cable length :1.8M) Quick Start Guide ViewSoinc Wizard CD-Rom	
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)	Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.	
		Warranty: Three-year limited warranty on parts, labor and backlight	
		UPC: 766907847710	
Operating Conditions:		Accessories:	
Temperature:	32-104° F (0-40° C)	CB-00009950, CB-00010555, CB-00010958, CS-xRi1, LCD-WMK-001, VSPF2700	
Humidity (non-condensing):	20-90%	Awards:	
Mount:		NO PAR	
VESA Compatible:	100 x 100 mm	E PC	
Video Signal:		VOICE	

Frequency Horizontal:	Analog: 15 ~ 130KHz; Digital: 15 ~ 90KHz		
Frequency Vertical:	Analog: 24 ~ 120Hz; Digital: 24 ~ 120Hz		
Video Input:			
Analog Sync:	CPU GIO for MHL / TMDS for HDMI 1.4 , PCI-E		

Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (01/31/2017 10:55 AM PST)