



HPE ProLiant MicroServer Gen8

Ideal first server: micro sized, big possibilities



- Collaborate
- Centralize
- Command

A quiet, cool-looking server that's easy on your wallet and great for your home and office

Most small and home businesses would benefit by having a server to improve their productivity and efficiency. But hesitate due to a lack of IT expertise and staff needed to install, configure, and maintain the necessary equipment.

You can take your business to the next level with the uniquely designed HPE ProLiant MicroServer Gen8. Our Intelligent Provisioning capability makes installation and setup a breeze making it your ideal first server solution. And its small, quiet, and cool design allows it to fit nicely into your existing home and office environments.

The HPE MicroServer comes with an optional purpose-built HPE PS1810 Switch and PS110 Wireless VPN Router solution that makes it easy for your business to enjoy all

the advantages of converged server and network-based computing—sharing files for greater efficiency and productivity, and the peace of mind of knowing that your important business data is protected. And by eliminating time-consuming backups of multiple client devices and consolidating data through a high-speed reliable network, our central server solution makes managing backups easier, while freeing up valuable time so you can focus on your business.

HPE ProLiant Gen8 value—worry-free management at its finest

HPE ProActive Insight Architecture inside each HPE ProLiant Server lets you monitor your network and it provides you with the tools that automate and simplify system provisioning, troubleshooting, and updates.

- Low energy
- Easy setup
- Quiet
- Cost efficient

HPE Integrated Lights-Out (iLO) 4 Management Engine provides a complete set of embedded management features to simplify management and increase server uptime. And for timesaving convenience, the optional new HPE iLO Essentials adds remote management capabilities so you can access your HPE MicroServer from anywhere and at any time via a web browser or mobile device.

- HPE Intelligent Provisioning—enables quick and easy setup including system configuration, deployment, and updating. Plus, everything you need is built into the server—no CDs or DVDs to load
- HPE Active Health System—maximizes your uptime as the HPE Active Health System proactively manages the health of your server 24x7 by predicting and avoiding failures that could lead to unplanned downtime
- Smart Update Manager—simplifies and consolidates updates according to your schedule. The built-in Smart Update Manager quickly and easily updates your firmware and system software
- Smart Memory—boosts data protection by increasing memory and resiliency
- iLO Essentials—remotely manage and troubleshoot your server from your desktop, mobile device, and from just about anywhere
- Integrated management on PS1810 Switch and PS110 Wireless VPN Router—PS1810 Switches and PS110 Wireless VPN Routers automatically discover and monitor the health status of ProLiant Gen8 servers via the iLO interface. This provides a single-pane-of-glass view of the servers and switch from one interface for remote management

Place it anywhere—the compact and quiet, HPE MicroServer stacked with the PS1810 Switch and PS110 Wireless VPN Router solution looks and works great, even in your front office

- Easy to set up and configure right out of the box
- Stacked, compact design looks as good as it works, and it emits little heat so you don't have to hide it away in a back office
- Runs quietly in the background with operating noise level of just 21 dBA to handle all your network and storage needs. The PS1810 Switch offers a fanless design

- Get all the power you need for fast, simultaneous access to files with an Intel® processor and 2 GB of RAM (expandable to 16 GB). The optional HPE PS1810-8G Switch supports “bonding” or “link aggregation” of the two Ethernet interfaces on the HPE MicroServer—doubling data speeds to the HPE MicroServer
- Save on your energy bill—the low wattage power supply helps you do more with less power. Green networking features of the PS1810-8G Switch saves on the cost of your network infrastructure

Consolidate your business information into one central server to eliminate chaos and help usher in productivity, collaboration, and security

- Move files off individual hard drives and onto the company drive for centralized access to everything you need to run your business
- Monitor and manage your server remotely with HPE iLO Essentials
- Control who has access to your files by setting up different levels of file permissions
- Keep your data protected under your own roof and not in a remote server farm or on individual PCs that are susceptible to viruses and malware

Seamless network connectivity increases simplicity and flexibility

- Integrated management with servers:
 - Compatible with purpose-built HPE PS1810 Switch Series and HPE PS110 Wireless VPN Router. The eight-port managed switch and the wireless router, both devices, can be stacked on top of the server for a clean and elegant solution
 - Single interface for monitoring status of all servers, routers, and switches in network
 - Automatic discovery of HPE ProLiant Gen8 servers on network
 - Link to iLO Management page for each server for advanced management
- High-speed reliable connection to HPE MicroServer—link aggregation doubles data speeds
- Fanless design for quiet operation
- Lifetime warranty

HPE ProLiant MicroServer Gen8

Technical specifications



Processor	Intel Celeron G1610T (2.3 GHz/2-core/2 MB/35 W) Processor Intel Pentium G2020T (2.5 GHz/2-core/3 MB/35 W) Processor Intel® Core™ i3-3240 (3.4 GHz/2-core/3 MB/55 W) Processor Intel® Xeon® E3-1220L v2 (2.3 GHz/2-core/3 MB/17 W) Processor					
Cache memory	3 MB (1 x 3 MB) L3 Cache for Xeon E3-1220L v2 3 MB (1 x 3 MB) L3 Cache for Core i3-3240 and Pentium G2020T 2 MB (1 x 2 MB) L3 Cache for Celeron G1610T					
Chipset	Intel C204 Chipset					
Management	HPE iLO Management Engine, HPE iLO Essentials (optional), HPE iLO Advanced (optional)					
Memory protection	ECC					
Memory	Type	HPE Smart Memory DDR3 Unbuffered (UDIMM)				
	DIMM slots available	2				
	Standard	4 GB (1 x 4 GB) PC3-12800E-11 DDR3 UDIMM				
	Maximum	16 GB (2 x 8 GB) PC3-12800E DDR3 UDIMM				
Network controller	HPE Ethernet 1Gb 2-port 332i Adapter					
Expansion slots	Expansion slot#	Technology	Bus width ¹	Connector width	Form factor	Notes
	1	PCIe 2.0	x16	x16	Low profile	
Storage controller	HPE Dynamic Smart Array B120i Controller for RAID 0/1/10 Optional HPE Smart Array P222 Controller with FBWC for RAID 5					
Internal storage devices	Optical drive				Optional: SATA DVD RW drive	
	Hard drives				Non-ship standard ²	
Maximum internal storage	Non-hot plug SATA			12 TB (4 x 3 TB) 3.5" SATA		
Interfaces	Video	1 rear standard video				
	USB 2.0 Ports	5 total (2 front, 2 rear, 1 internal)				
	USB 3.0 Ports	2 total (2 rear)				
	Network RJ45 (Ethernet)	Note: Functional after OS boot 2 (port 1 shared for HPE iLO 4 as optional configuration)				
	HPE iLO Remote Management Network Port	1 Gb dedicated (default iLO 4 configuration)				
	microSD slot	1 (internal)				
Graphics	Integrated Matrox G200 video standard					
	<ul style="list-style-type: none"> • 1280 x 1024 (32 bpp) • 1920 x 1200 (16 bpp) 					
	HPE iLO 4 On System Management Memory					
	<ul style="list-style-type: none"> • 16 MB flash • 256 MB DDR3 with ECC (112 MB after ECC and video) 					

¹ Indicates the number of physical electrical lanes running to a PCIe connector.

² Some stock-keeping units (SKUs) include hard disk drives (HDDs). To learn more, visit hp.com/go/microserver

Technical specifications (continued)

Form factor	Ultra Micro Tower
Industry standard compliance	ACPI v2.0 compliant PCI (Peripheral Component Interconnect) 2.3 compliant PxE (preboot execution environment) support WOL (Wake on LAN) support IPMI (Intelligent Platform Management Interface) 2.0 compliant USB (Universal Serial BUS) 2.0 USB (Universal Serial BUS) 3.0 SATA (Serial ATA) Gen2
Security	Setup password
Server power cords	The MicroServer models ship standard with a 6" country-specific National Electrical Manufacturers Association (NEMA) power cord. If customers require an alternative local power cord, they can check the power cord matrix for the appropriate country-specific SKU. Please see the following power cord matrix: hp.com/go/powercordmatrix
Power supply	150 watts non-hot plug, non-redundant power supply (AMS and APJ models) 200 watts non-hot plug, non-redundant power supply (EMEA models)
System fans	One (1)—non-redundant system fan shipped standard
Operating systems	Microsoft® Windows Server® Red Hat® Enterprise Linux® (RHEL) SUSE Linux Enterprise Server (SLES) VMware®
Power specifications	To review typical system power ratings, use the HPE Power Advisor, which is available via the online tool located at hp.com/go/hppoweradvisor

Optimize your IT investment strategy with new ways to acquire, pay for and use technology, in lock-step with your business and transformation goals. hp.com/solutions/hpefinancialservices

Network switch accessory

HP PS1810-8G Switch: hp.com/go/ps1810

Network router accessory

HP PS110 Wireless VPN Router: hp.com/go/ps110

Services and support

You can now get the support you need by choosing from one of a number of support options designed to address your unique needs. To find the support service right for you, visit hp.com/go/supportservices.

Learn more at hp.com/go/microserver



Sign up for updates

© Copyright 2013–2016 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Intel Xeon, Intel Core, Pentium, and Celeron are trademarks of Intel Corporation in the U.S. and other countries. Microsoft and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Red Hat is a registered trademark of Red Hat, Inc. in the United States and other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. microSD is a trademark or registered trademark of SD-3C in the United States, other countries or both. VMware is a registered trademark or trademark of VMware, Inc. in the United States and/or other jurisdictions. All other third-party trademark(s) is/are the property of their respective owner(s).