

Key Features


10-point Projected Capacitive Touch | SuperClear® MVA-type panel technology | Frameless Design | Versatile Connectivity | Durable, Scratch-resistant Screen



Product Description

Laid flat or angled for customized comfort, this display delivers touchscreen versatility to the max. Offering fantastic flexibility for retail, education, or business settings, the ViewSonic® TD2430 is a 24" (23.6" viewable) Full HD display with 10-point multi-touch functionality. Delivering adjustable positioning, wide-angle viewing, and a durable design, the TD2430 has everything to accommodate your unique needs. Adding even more convenience, cross-compatibility with a wide range of operating systems includes Windows 10, and certain Android and Linux versions.* With a sleek edge-to-edge screen and frameless bezel, this intuitive touchscreen performs like your favorite tablet or smartphone to deliver a highly accurate, ultra-responsive touch experience ideal for interactivity in public environments, kiosk and wayfinding applications, classroom settings, and more. *Supports Windows 7/8/10, Linux 2.6.38 or later, and Android 4.0 or later.





24"
DISPLAY



MVA
PANEL



1920 x 1080
RESOLUTION

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Type:	MVA
Colors:	16.7M
Static Contrast Ratio:	3000:1
Viewing Angles:	178° horizontal, 178° vertical
Resolution:	1920 x 1080
Viewable Area (in.):	23.6
Dynamic Contrast Ratio:	50,000,000:1
Backlight Life (Hours):	40,000
Response Time (GTG):	25ms
Light Source:	WLED
Brightness:	250 cd/m2
Panel Surface:	7H Scratch Resistant Surface Hardness
Aspect Ratio:	16:9
Display Size (in.):	24

Compatibility:

PC Resolution (max):	1920 x 1080
----------------------	-------------

Touch:

Technology:	Projective Capacitive
Touch Points:	10

Connector:

USB 3.0 Type A(2), USB 3.0 Type B(1), VGA(1), HDMI 1.4(1), Display Port(1)
--

Audio:

Internal Speakers:	2.5W (x2)
--------------------	-----------

Video Signal:

Frequency Horizontal:	Analog: 24 ~ 82KHz, Digital: 50 ~ 76Hz
Frequency Vertical:	Analog: 15 ~ 82KHz, Digital: 50 ~ 76Hz
Analog Sync:	Separate Sync / Composite Sync / Sync on Green, TMDS, PCI-E

Power:

Eco Mode (Conserve):	19W
Eco Mode (optimized):	22W
Consumption (typical):	25W
Consumption (max):	28W
Voltage:	AC 100-240V (universal), 50-60Hz

Operating Conditions:

Temperature:	32-104° F (0-40° C)
Humidity (non-condensing):	20-90%

Ergonomics:

Tilt (Forward/Back):	20° - 53°, 90° (Flat)
----------------------	-----------------------

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Mount:

VESA Compatible:	100 x 100 mm
------------------	--------------

Weight (metric):

Gross (kg):	5.4
Net Without Stand (kg):	7.1

Weight (imperial):

Net (lbs):	11.6
Gross (lbs):	15.6

Dimensions (metric) (WxHxD):

Packaging (mm):	643 x 435 x 140
Physical (mm):	573 x 353 x 47

Dimensions (imperial) (WxHxD):

Packaging (in.):	25.3 x 17.1 x 5.5
Physical (in.):	22.6 x 13.9 x 1.9

General:

Regulations: cTUVus, FCC-B w/ ICES003, DOE Energy Star 7.0, DOE EPEAT Silver, TUV-MX-CoC, Mexico Energy

PACKAGE CONTENTS: LCD Display AC/DC Adapter Power Cable (1.5m) HDMI Cable (1.5m) USB3.0 Upstream Cable (1.5m) Audio Cable (1.5m) Quick Start Guide ViewSonic Wizard CD-ROM

Warranty: Three-year limited warranty on parts, labor and backlight

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907846911

Accessories:

CB-00008948, CB-00009950, CB-00010555, CB-00010684, CB-00010958, LCD-CABLE-001, LCD-WMK-001, VSPF2360, cb-00011486

Awards:

Stand-by: 0.5W

Controls:

Physical Controls: 1, 2, Up, Down, Power

On Screen Display:

Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (01/31/2017 03:06 PM PST)