



HP PageWide XL Folder

High-productivity online folding for the HP PageWide XL 8000 Printer and the HP PageWide XL 5000 Printer series



Full online integration

- Control the folder and folding styles from HP SmartStream software, the driver, the scanner, or the printer touchscreen
- Bi-directional communication between the printer and the folder enables reliable operation
- Monitor folder status from the printer or the HP SmartStream software; the job queue halts when the folder has stopped

High speed

- The HP PageWide XL Folder is designed to match the breakthrough productivity of HP PageWide XL printers
- Stack up to 150 A0/E-size folded packages

Versatility

- Opt for the standard HP PageWide XL Folder or for the HP PageWide XL Folder with Tab Applicator if you need to apply reinforcement strips to your documents
- Fold up to 914 mm (36 in) in width and up to 2.5 m (8.2 ft) in length for fully folded packages; fan fold up to 6 m (19.7 ft) in length; add the HP PageWide XL Folder Upgrade Kit for Long Plots for unlimited length fan folding
- Choose from pre-defined folding programs or create your custom folding styles
- Supports DIN, AFNOR, ANSI, and US folding standards

For more information, please visit
hp.com/go/pagewidexlsolutions

Technical specifications


HP PageWide XL Folder

Paper handling	Paper feed	Automatic or manual	
	Paper width	297 to 914 mm (11 to 36 in)	
	Paper length (fan fold)	Up to 6,000 mm (19.7 ft) Unlimited with the HP PageWide XL Folder Upgrade Kit for Long Plots	
	Paper length (cross fold)	Up to 2,500 mm (8.2 ft)	
	Paper weight (folding)	75 to 90 g/m ² (20 to 24 lb)	
	Paper type (folding)	Plain paper, bond paper	
	Output delivery	Standard belt, capacity for up to 150 A0/E-size folded packages	
	Stacking on folder	Up to 10 pages, up to A0/E-size	
	Folding	Fan fold	180 to 297 mm (increments of 1 mm) (7 to 11 in (increments of 0.03 in)) Binding margin adjustable 0 to 30 mm (increments of 1 mm) (0 to 1.1 in (increments of 0.03 in))
		Cross fold	Z-style; panel length 280 mm to 310 mm (11 to 12.2 in)
Folding programs		DIN B 210x297 DIN C 210x297 DIN B 210x305 DIN B 210x310 Fan Fold only DIN A 190/20x297 DIN 185/25x297 INVERSE DIN 210x297 AFNOR 297x210 ANSI 8.5x11 ANSI 7.5+1x11 ARCH 9.0x12 Mailer 7.5x10 Fan Fold only 9.0	
Dimensions		Dimensions with packaging	1850 x 1070 x 1420 mm (72 x 42 x 55 in)
		Dimensions without packaging	1800 x 1620 x 1220 mm (70 x 63 x 48 in)
Weight		Weight with packaging	365 kg (804 lb)
		Weight without packaging	310 kg (683 lb)
Environmental		Operating temperature	10 to 40°C (50 to 104 °F)
		Recommended temperature	15 to 35°C (59 to 95°F)
		Operating humidity	20% to 80% RH, depending on media type
Acoustic¹	Sound pressure	63 dB(A) (printing), 35 dB(A) (ready), < 25 dB(A) (sleep)	
	Sound power	8 B(A) (printing), 5.1 B(A) (ready), < 4.2 B(A) (sleep)	
Power	Power requirements	300 kW (typical)	
	Requirements	Input voltage (auto ranging) 100-120/200-240 ± 10% VAC, 50/60 ± 3 Hz, 10/5 A	
Certifications	Safety	IEC 60950-1+A1+A2 compliant; USA and Canada; EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC)	
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KC)	
	Environmental	CE marking (including RoHS, WEEE, REACH)	
Ordering	Product number	K5H75A	
	Options	MOV04A HP PageWide XL Folder Upgrade Kit for Long Plots	
Warranty	Standard warranty		


¹Acoustics based on the HP PageWide XL 8000 Printer with the HP PageWide XL Folder.

HP PageWide XL Folder with Tab Applicator


Paper handling	Paper feed	Automatic or manual	
	Paper width	297 to 914 mm (11 to 36 in)	
	Paper length (fan fold)	Up to 6,000 mm (19.7 ft) Unlimited with the HP PageWide XL Folder Upgrade Kit for Long Plots	
	Paper length (cross fold)	Up to 2,500 mm (8.2 ft)	
	Paper weight (folding)	75 to 90 g/m ² (20 to 24 lb)	
	Paper type (folding)	Plain paper, bond paper	
	Output delivery	Standard belt, capacity for up to 150 A0/E-size folded packages	
	Stacking on folder	Up to 10 pages, up to A0/E-size	
	Folding	Fan fold	180 to 297 mm (increments of 1 mm) (7 to 11 in (increments of 0.03 in)) Binding margin adjustable 0 to 30 mm (increments of 1 mm) (0 to 1.1 in (increments of 0.03 in))
		Cross fold	Z-style; panel length 280 mm to 310 mm (11 to 12.2 in)
Folding programs		DIN B 210x297 DIN C 210x297 DIN B 210x305 DIN B 210x310 Fan Fold only DIN B 210 TAB DIN B 198 TAB DIN A 190/20x297 DIN 185/25x297 INVERSE DIN 210x297 AFNOR 297x210 ANSI 8.5x11 ANSI 7.5+1x11 ARCH 9.0x12 Mailer 7.5x10 Fan Fold only 9.0	
Dimensions		Dimensions with packaging	2180 x 1070 x 1420 mm (85.8 x 42 x 55 in)
		Dimensions without packaging	2100 x 1620 x 1220 mm (82 x 63 x 48 in)
Weight		Weight with packaging	410 kg (903 lb)
		Weight without packaging	360 kg (793 lb)
Environmental		Operating temperature	10 to 40°C (50 to 104 °F)
		Recommended temperature	15 to 35°C (59 to 95°F)
		Operating humidity	20% to 80% RH, depending on media type
Acoustic¹	Sound pressure	63 dB(A) (printing), 35 dB(A) (ready), < 25 dB(A) (sleep)	
	Sound power	8 B(A) (printing), 5.1 B(A) (ready), < 4.2 B(A) (sleep)	
Power	Power requirements	300 kW (typical)	
	Requirements	Input voltage (auto ranging) 100-120/200-240 ± 10% VAC, 50/60 ± 3 Hz, 10/5 A	
Certifications	Safety	IEC 60950-1+A1+A2 compliant; USA and Canada; EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC)	
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KC)	
	Environmental	CE marking (including RoHS, WEEE, REACH)	
Ordering	Product number	L3M58A	
	Options	MOV04A HP PageWide XL Folder Upgrade Kit for Long Plots	
Warranty	Standard warranty		



Standard folding packages



Standard folding packages with reinforcement stripe



Standard folding packages with binding edge